

TSRS485 Reader-GSM4

Datasheet

The **TSRS485 Reader- GSM4** is Reliable, Flexible and Plug-n-play device to read data over RS485 (Modbus RTU) from any device and transmit that data securely to other devices over 4G/LTE Network using various IoT protocols (MQTT). Modbus RTU and MQTT protocol handling are integrated into GPRS module for better reliability. This enables this device to use powerful CPU and more memory resources to make Module's software architecture flexible and robust. Most innovative and unique design on Quectel EC25-E without using any external microcontroller.

For additional information, updated documentation, and a list of accessories, contact us at support@thingslista.com.



Specifications

4G/LTE Modem

- Quectel EC25-E Processor
- LTE, UMTS/HSPA (+) and GSM/GPRS/EDGE
- Bandwidth:1.4/3/5/10/15/20MHz
- Frequency: FDD LTE: B1/B3/B5/B7/B8/B20 TDD LTE: B38/B40/B41 WCDMA: B1/B5/B8 GSM: 900/1800
- Multi-constellation GNSS(Global Navigation Satellite System) receiver
- Recommended operating temperature range: -40 °C ~ +85 °C
- Antenna DL MIMO, supports Rx-diversity

Power Requirements

- 9-24VDC/2A

Accessories

- Modbus RTU MQTT Gateway
- 12V/2A Power Adapter
- GSM 2 DBI rubber duck antenna
- GPS/GLONASS GNSS Antenna With 3 Mtr Cable

Features

1. Flexible firmware design and architecture
2. Easy to change firmware logic as per client requirement
3. Supports parallel RS485 (Modbus Read/Write RTU) transactions
4. Designed around Quectel EC25 is a series of LTE Cat 4 module
5. 150Mbps downlink and 50Mbps uplink data rates
6. GNSS receiver available for applications requiring fast and accurate GPS Positioning in any environment
7. Standard JSON payload output
8. Supports up to 800 tags (Modbus registers) in total (Multiple transactions)
9. Supports up to 40 tags (Modbus registers) per transaction (Max Transaction 20)
10. Configurable data transmission interval
11. Limited data buffering on board to avoid data loss during failover
12. Extensible data buffering using micro SD card for larger data buffering capabilities
13. Robust failover handling.
 - a. Auto reconnect with endpoint.
 - b. Auto reboot if required (no signal or connection fails repeatedly).
14. Externalized configuration parameters
 - a. MQTT Broker URL/IP, Port no, Username & Password,
 - b. RS485 Baud rate for serial port (2400, 4800, 9600, 19200, 38400, 57600, 115200)
15. Secure data transmission over SSL/TLS

Warranty

Thingslista IoT warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Thingslista IoT will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the product.

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE. This Warranty is exclusive and limited to repair or, at the discretion of Thingslista IoT, replacement. IN NO EVENT SHALL THINGSLISTA BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.

Thingslista IoT, reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Thingslista IoT Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Thingslista IoT will void the product warranties. All specifications published in this document are subject to change; Thingslista IoT reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language.